

Pressure	bar(g)	8	10	12
1st row: Free air delivery* (m ³ /min)	8	5,29		
		33,44		
		41,70		
2nd row: Shaft Power* (kW)	10			4,46
				33,73
				40,56
3rd row: Terminal Power (incl. Fan)* (kW)	12			4,17
				35,15
				41,00
Sound Level	dB(A)	68 +/-2		
Air Discharge Temperature over Ambient	K	≤15		
Tank for TD version	l	-		
Controller	MAM-6080			
Electrical Data				
Voltage / Frequency	400V / 50Hz			
Rated Motor Power	kW	30		
Motor speed	1/min	2940		
Starting method	Star/Delta			
Efficiency Class	IE-3			
Enclosure / ISO Class	IP 54 / F			
Rated Fan Motor Power	kW	1,1		
Fan Drive	Fixed			
Rated Dryer Power	kW	-		
Recommned cross-section, lenght 10M	25mm ²			
Fuse (Type gG)	A	80		
Cooling Data				
Type of cooling	Air Cooling			
Cooling air capacity	m ³ /h	4.500		
Ambient Temperature	°C	+5 - +45		
Dimensions, Weight ...				
Dimension Stand Alone (l x w x h)	mm	1530 x 970 x 1350		
Dimension with Tank&Dryer (l x w x h)	mm	-		
Weight Stand Alone	kg	760		
Weight with Tank&Dryer	kg	-		
Compressed Air Outlet Stand Alone	1 1/2"			
Compressed Air Outlet Tank&Dryer	-			
Oil Capacity	l	22		
Residual Oil Content	mg/m ³	3-5		

* Measurement of data according to ISO1217 Annex C / E

Technical changes reserved.

Copyright@Tolpec GmbH